

FF28LWHMED2



26.63" x 18.5" x 17.75" (H x W x D)

Compact auto defrost medical/scientific all-refrigerator with digital thermostat, NIST calibrated thermometer/alarm, front lock, hospital grade cord, and internal fan

Highlights:

Specially designed and featured to meet the CDC, VFC and VFA's guidelines for safe vaccine storage

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Assembled in the USA from domestic and imported components

Product Features:

Reliable temperature stability	Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines
Factory installed lock	Keyed lock for added security, with two keys included
Automatic defrost	Reduced maintenance with auto defrost system
Internal fan	Fan-forced cooling ensures the unit is evenly cooled from top to bottom
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials

FF28LWHMED2 Specifications:

Overview	
Nominal Height	27.0" (69 cm)
Height of Cabinet	26.63" (68 cm)
Nominal Width	19.0" (48 cm)
Width	18.5" (47 cm)
Nominal Depth	18.0" (46 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	2.4 cu.ft. (68 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.7
Voltage/Frequency	115 V AC/60 Hz
Weight	45.0 lbs. (20 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101056456
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.7oz.
High Side PSI	120.0
Low Side PSI	70.0
Level Legs Qty	2
Temperature Range	2 to 8°C
Dimensions	
Interior Height	20.5" (52 cm)
Interior Width	15.5" (39 cm)
Interior Depth	13.5" (34 cm)
Compressor Step Height	7.75" (20 cm)

Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	5.5" (14 cm)

