

# ACR1602G



76.75" x 23.38" x 28" (H x W x D)

Upright healthcare all-refrigerator with self-closing glass door, front lock, digital controls, and external temperature readout

## Highlights:

Designed and constructed for reliable cold storage in healthcare facilities

Factory installed lock provides security you can count on

Self-closing door protects interior products from ambient temperatures


## Product Features:

|                              |                                                                                                                                                                                                                                                 |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EQTemp Medical Refrigerator  | All-refrigerator designed to operate between 2 and 8°C for a variety of storage application in medical offices and other healthcare facilities                                                                                                  |
| Temperature Range: 2° to 8°C | Preset to 5°C as recommended for many storage applications                                                                                                                                                                                      |
| Large capacity               | Complete 15.53 cu.ft. capacity inside conveniently slim footprint                                                                                                                                                                               |
| External temperature readout | Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button                                                                                           |
| High/low temperature alarm   | Audible alarm sounds if the interior temperature rises or falls out of set range                                                                                                                                                                |
| Buffered temperature probe   | Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines |
| Access port                  | 3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of user-provided monitoring equipment                                                                                                                     |
| Commercial design            | Meets UL-471 commercial standards                                                                                                                                                                                                               |
| Factory installed lock       | Keyed lock for a secure interior (2 keys included)                                                                                                                                                                                              |


## ACR1602G Specifications:

| Overview                   |                      |
|----------------------------|----------------------|
| Nominal Height             | 77.0" (196 cm)       |
| Height of Cabinet          | 76.75" (195 cm)      |
| Nominal Width              | 24.0" (61 cm)        |
| Width                      | 23.38" (59 cm)       |
| Width with Door Open       | 23.63" (60 cm)       |
| Nominal Depth              | 28.0" (71 cm)        |
| Depth                      | 28.0" (71 cm)        |
| Depth with door at 90°     | 50.0" (127 cm)       |
| Capacity                   | 15.53 cu.ft. (440 L) |
| Defrost Type               | Automatic            |
| Door                       | Glass                |
| Cabinet                    | White                |
| US Electrical Safety       | ETL                  |
| Canadian Electrical Safety | ETL-C                |
| Amps                       | 2.0                  |
| Voltage/Frequency          | 115 V AC/60 Hz       |
| Weight                     | 176.4 lbs. (80 kg)   |
| Parts & Labor Warranty     | 1 Year               |
| Compressor Warranty        | 5 Years              |
| UPC                        | 761101083049         |
| Refrigerator Features      |                      |
| Door Swing                 | RHD                  |
| Reversible                 | Factory Reversible   |
| Shelf Type                 | Wire                 |
| Shelf Qty                  | 6                    |
| Adjustable Shelves         | Yes                  |
| Thermostat Type            | Digital              |
| Refrigerant Type           | R600a                |
| Refrigerant Amount         | 2.4oz.               |
| High Side PSI              | 1.45                 |
| Low Side PSI               | 0.85                 |
| Level Legs Qty             | 2                    |
| Interior Light             | Yes                  |
| Temperature Range          | 2° to 8°C            |
| Sound Level                | 38.8 dB              |
| Dimensions                 |                      |
| Interior Height            | 68.25" (173 cm)      |

|                        |               |
|------------------------|---------------|
| Interior Width         | 20.0" (51 cm) |
| Interior Depth         | 21.5" (55 cm) |
| Compressor Step Height | 9.0" (23 cm)  |
| Compressor Step Width  | 20.0" (51 cm) |
| Compressor Step Depth  | 8.0" (20 cm)  |



Top



Front