

# ACR52GNSF456LHD



34" x 23.5" x 21.75" (H x W x D)

Built-in healthcare all-refrigerator certified to NSF/ANSI 456 with self-closing glass door, front lock, digital controls, and NIST calibrated temperature readout

## Highlights:

Certified to NSF/ANSI 456 Vaccine Storage Standard

Specially designed to meet current CDC/VFC/VFA vaccine refrigeration guidelines for convenient storage in pharmacies, medical offices, and other healthcare facilities

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

## Product Features:

|  |   |
|--|---|
| EQTemp Medical Refrigerator                        | All-refrigerator designed to operate between 2 and 8°C for a variety of storage application in medical offices and other healthcare facilities  |
| Certificate of calibration included                | The temperature monitoring device (TMD) is calibrated to NIST standards in our ISO/IEC 17025:2017 certified calibration laboratory and ships with a 2-year certificate of calibration for your records  |
| Certified to NSF/ANSI 456 Vaccine Storage Standard | Tested to comply with the latest standards  |
| Temperature Range: 2° to 8°C                       | Preset to 5°C as recommended for many storage applications  |
| External temperature readout                       | Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button   |
| High/low temperature alarm                         | Audible alarm sounds if the interior temperature rises or falls out of set range  |
| Built-In capable                                   | Front-breathing design lets you make the best use of space by installing your appliance under the counter   |
| Buffered temperature probe                         | Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines |



## ACR52GNSF456LHD Specifications:

| Overview                   |                     |
|----------------------------|---------------------|
| Nominal Height             | 34.0" (86 cm)       |
| Height of Cabinet          | 34.0" (86 cm)       |
| Nominal Width              | 24.0" (61 cm)       |
| Width                      | 23.5" (60 cm)       |
| Width with Door Open       | 23.75" (60 cm)      |
| Nominal Depth              | 22.0" (56 cm)       |
| Depth                      | 21.75" (55 cm)      |
| Depth with door at 90°     | 43.75" (111 cm)     |
| Capacity                   | 3.88 cu.ft. (110 L) |
| Defrost Type               | Automatic           |
| Door                       | Glass               |
| Cabinet                    | White               |
| US Electrical Safety       | ETL                 |
| Canadian Electrical Safety | ETL-C               |
| Sanitation                 | ETL-S to NSF 456    |
| Amps                       | 2.0                 |
| Voltage/Frequency          | 115 V AC/60 Hz      |
| Weight                     | 91.5 lbs. (42 kg)   |
| Parts & Labor Warranty     | 1 Year              |
| Compressor Warranty        | 5 Years             |
| UPC                        | 761101107769        |
| Refrigerator Features      |                     |
| Door Swing                 | LHD                 |
| Reversible                 | Factory Reversible  |
| Shelf Type                 | Wire                |
| Shelf Qty                  | 3                   |
| Adjustable Shelves         | Yes                 |
| Thermostat Type            | Digital             |
| Fan Type                   | Interior            |
| Refrigerant Type           | R600a               |
| Refrigerant Amount         | 1.23oz.             |
| High Side PSI              | 1.45                |
| Low Side PSI               | 0.85                |
| Level Legs Qty             | 2                   |
| Interior Light             | Yes                 |
| Temperature Range          | 2° to 8°C           |
| Sound Level                | 42 dB               |

| Dimensions             |                |
|------------------------|----------------|
| Interior Height        | 25.88" (66 cm) |
| Interior Width         | 18.75" (48 cm) |
| Interior Depth         | 16.5" (42 cm)  |
| Compressor Step Height | 4.0" (10 cm)   |
| Compressor Step Width  | 18.75" (48 cm) |
| Compressor Step Depth  | 11.5" (29 cm)  |

