### accuc@ld

# **AFZ5PVBIADADL2BLHD**



31.75" x 23.38" x 25" (H x W x D)

Performance series Pharma-Vac 4 cu.ft. ADA height purpose-built vaccine storage freezer designed for recessed or freestanding installation, with factory-installed NIST calibrated temperature logger (DDL)

#### **Highlights:**

NIST calibrated DDL included for accurate temperature logging

Sized just under 32" high to fit under lower ADA compliant counters

Intelligent microprocessor digital temperature controller

#### **Product Features:**

Performance Series freezer	Purpose-built all-freezer for vaccine storage in medical, pharmaceutical, and life science applications	
Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines	
ADA Compliant	Just under 32" tall designed to fit under ADA compliant counters	
Recessed or freestanding use	Versatile design allows recessed installation under counters or freestanding use	
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Digital data logger (DDL) included	Accucold DL2B data logger is NIST calibrated in our ISO/IEC 17025:2017 laboratory, with user-set logging intervals, a large LCD readout of the current and high/low temperature, and virtually unlimited storage through internal memory and a convenient USB drive; for additional information on this logger's features, view the DL2BKit on our website	
Commercial design	Meets UL-471 commercial standards	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between -30°C to -10°C	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
ACCUCOLD DIVISION, FELIX STORCH, IN	IC.   ISO 9001:2015 Certified	



## accuc@ld

### AFZ5PVBIADADL2BLHD Specifications:

Overview			
Nominal Height	32.0" (81 cm)		
Height of Cabinet	31.75" (81 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.38" (59 cm)		
Width with Door Open	23.88" (61 cm)		
Nominal Depth	25.0" (64 cm)		
Depth	25.0" (64 cm)		
Depth with Handle	26.75" (68 cm)		
Depth with door at 90°	47.0" (119 cm)		
Capacity	3.88 cu.ft. (110 L)		
Defrost Type	Manual		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Amps	1.3		
Voltage/Frequency	115 V AC/60 Hz		
Weight	125.0 lbs. (57 kg)		
Parts & Labor Warranty	2 Years		
Compressor Warranty	5 Years		
UPC	761101104089		
Freezer			
Door Swing	LHD		
Reversible	No		
Interior Height	22.5" (57 cm)		
Interior Width	18.0" (46 cm)		
Interior Depth	18.0" (46 cm)		
Shelf Type	Wire		
Shelf Qty	4		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Interior Light	Yes		
Refrigerant Type	R290		
	R290 1.73 oz.		
Refrigerant Type			
Refrigerant Type Refrigerant Amount	1.73 oz.		

Compressor Step Width	18.0" (46 cm)
Compressor Step Depth	7.13" (18 cm)
Temperature Range	-30 to -10°C



