

# ARG12PV456



61.75" x 23.38" x 24.38" (H x W x D)

Performance series Pharma-Vac 12 cu.ft. upright glass door all-refrigerator certified to NSF/ANSI 456 Vaccine Storage Standard

## Highlights:

Certified to NSF/ANSI 456 Vaccine Storage Standard

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

## Product Features:

Certified to NSF/ANSI 456 Vaccine Storage Standard    Designed and tested to comply with the new NSF Vaccine Storage Standard

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Certificate of calibration included	2-year calibration certificate included for your records
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup

## ARG12PV456 Specifications:

Overview	
Nominal Height	62.0" (157 cm)
Height of Cabinet	61.75" (157 cm)
Nominal Width	24.0" (61 cm)
Width	23.38" (59 cm)
Width with Door Open	23.88" (61 cm)
Nominal Depth	25.0" (64 cm)
Depth	24.38" (62 cm)
Depth with Handle	26.13" (66 cm)
Depth with door at 90°	46.5" (118 cm)
Capacity	12.0 cu.ft. (340 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S to NSF 456
Amps	1.4
Voltage/Frequency	115 V AC/60 Hz
Weight	190.0 lbs. (86 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101090573
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	7
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	2.11oz.
Interior Light	Yes
Temperature Range	2 to 8°C
Dimensions	
Interior Height	53.0" (135 cm)
Interior Width	20.0" (51 cm)

Interior Depth	17.0" (43 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	20.0" (51 cm)
Compressor Step Depth	5.0" (13 cm)

