### accuc@ld

# **ARG2PV-CRT**



22.25" x 18.5" x 23.25" (H x W x D)

Performance series 2 cu.ft. countertop glass door controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

#### **Highlights:**

Adjustable operating control range from 68 to 77°F (preset to 72°F)

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at  $72^{\circ}F$ 

Intelligent microprocessor digital temperature controller

#### **Product Features:**


Controlled Room Temperature Cabinet	Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72°F	
Purpose-built design	Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products	
+/-1.5°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period	
Stable operation	Designed to maintain a set temperature, even when ambient room temperature is as cold as $68^{\circ}\text{F}$ or as high as $86^{\circ}\text{F}$	
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread	
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +68 to +77°F	
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range	
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)	
Automatic defrost with adjustable cycle  ### Automatic defrost with adjustable cycle  #### Automatic defrost with adjustable cycle  ###################################	1 2	

## accuc@ld

### **ARG2PV-CRT Specifications:**

Overview	
Nominal Height	23.0" (58 cm)
Height of Cabinet	22.25" (57 cm)
Nominal Width	19.0" (48 cm)
Width	18.5" (47 cm)
Width with Door Open	18.88" (48 cm)
Nominal Depth	24.0" (61 cm)
Depth	23.25" (59 cm)
Depth with Handle	24.75" (63 cm)
Depth with door at 90°	42.5" (108 cm)
Capacity	1.94 cu.ft. (55 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	80.0 lbs. (36 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101106960
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	2
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.84oz.
High Side PSI	280.0
Low Side PSI	90.0

Temperature Range	68 to 77°F (preset to 72°F)
Sound Level	42.4 dB
Dimensions	
Interior Height	16.5" (42 cm)
Interior Width	15.25" (39 cm)
Interior Depth	15.75" (40 cm)
Compressor Step Height	8.25" (21 cm)
Compressor Step Width	15.25" (39 cm)
Compressor Step Depth	4.25" (11 cm)







FRONT VIEW