

ARS32PVBIADA-CRT



32" x 19.75" x 22.63" (H x W x D)

Performance series 2.83 cu.ft. upright ADA height controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

Highlights:

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Adjustable operating control range from 68 to 77°F (preset to 72°F)

32" height fits under lower ADA compliant counters

Product Features:

| | |
|-------------------------------------|--|
| Controlled Room Temperature Cabinet | Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72°F |
| Purpose-built design | Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079 > Good Storage and Distribution Practices for Drug Products |
| ADA Compliant | 32" height is designed to fit under ADA compliant counters |
| +/-1.5°C Variation | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Stable operation | Designed to maintain a set temperature, even when ambient room temperature is as cold as 68°F or as high as 86°F |
| Recessed or freestanding use | Versatile design allows recessed installation under counters or freestanding use |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between +68 to +77°F |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| Remote alarm contacts | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) |

ARS32PVBIADA-CRT Specifications:

| Overview | |
|------------------------------|--------------------|
| Nominal Height | 32.0" (81 cm) |
| Height of Cabinet | 32.0" (81 cm) |
| Nominal Width | 20.0" (51 cm) |
| Width | 19.75" (50 cm) |
| Width with Door Open | 20.25" (51 cm) |
| Nominal Depth | 23.0" (58 cm) |
| Depth | 22.63" (57 cm) |
| Depth with Handle | 24.38" (62 cm) |
| Depth with door at 90° | 40.0" (102 cm) |
| Capacity | 2.83 cu.ft. (80 L) |
| Defrost Type | Automatic |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 0.75 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 92.0 lbs. (42 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101090528 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Yes |
| Shelf Type | Wire |
| Shelf Qty | 4 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 1.41oz. |
| High Side PSI | 280.0 |
| Low Side PSI | 90.0 |
| Interior Light | Yes |

Temperature Range 68 to 77°F (preset to 72°F)

| Dimensions | |
|------------------------|----------------|
| Interior Height | 24.0" (61 cm) |
| Interior Width | 16.0" (41 cm) |
| Interior Depth | 15.0" (38 cm) |
| Compressor Step Height | 6.13" (16 cm) |
| Compressor Step Width | 15.25" (39 cm) |
| Compressor Step Depth | 5.5" (14 cm) |

