



ScienTempTM

Low Temperature Freezer



Versatile Design—Standard Models or we can custom design one that meets your needs

Safety & Easy Access - Counter-balanced lid with magnetic gasket. Brushed aluminum and thermoplastic tubular handle with separate Keyed Hasp Lock. Inner Styrofoam Sub-lids are included for additional protection of content.

Safe & Economical Insulation— Our freezers are insulated using environmentally safe PFAS-free Ecofoam Polyurethane Foam.

CFC Free Refrigerant - All products are manufactured using CFC-free, non-toxic, non-combustible and non-ozone depleting refrigerant. Compressors are permanently lubricated and hermetically sealed for easy maintenance.

Sturdy Construction - Cabinets are welded steel with a textured exterior / smooth interior powdercoat finish.

Comfortable Access - Low-profile design. Controls are conveniently mounted on the front of an end rack for easy access

Casters - Locking 3" heavy duty swivel type casters

****Note:** Can install leveling legs in place of Casters

Model 85-3.1EX Explosion Proof

Class 1, Division 1, Group C & D
Class 1, Division 2, Group C & D

Exterior Dimensions	37"H x 59"W x 24"D
Interior Dimensions	14"H x 30"W x 13"D
Temperature Range	-45°C to -85°C / -50°F to -121°F
Capacity	3.1 cubic feet
Insulation	Polyurethane
Door	Keyed Hasp Lock
Casters	(4) 2" Locking or (4) Leveling Legs
Temperature Controller	Analog Dial

**Exterior height includes casters

**Depth measurement includes hinges and handle.

Refrigeration

Compressor	1/2 hp
Refrigerant	R-513A High Stage / R-508B Low Stage
Voltage Options	115/60/1 - 230/60/1 - 230/50/1
Refrigerant Control	Capillary Tube
Evaporator	Cold Wall
Defrost	Manual
Air Circulation	Gravity
Running Amps	12 amps (115V) 6 amps (230V)

Optional Accessories

- Access Ports (1", 2" or 4" are available)
- Stainless Steel Interior and / or Exterior

Scientemp Corporation 3565 S. Adrian Hwy Adrian, MI 49221 Ph: 517-263-6020

www.scientemp.com

January 2026