

MODEL C40-14X

EXPLOSION PROOF CHEST FREEZER 0°C TO -40°C

Capacity [Cu. Ft.] 14 Cu. Ft.
Capacity [Liters] 400 Liters
Temperature Range [°C] 0°C to -40°C
Temperature Range [°F] 32°F to -40°F

Dimensions Width x Depth x Height
Exterior [Inches] 72.5" x 37" x 47.5"
Interior [Inches] 62" x 20" x 20"
Exterior [Centimeters] 184 x 93 x 120
Interior [Centimeters] 157 x 50 x 50

Refrigeration System Single Stage System
Compressors 1, Hermetic Compressor
Compressor Container Explosion Proof
Air Circulation Gravity Flow
Defrost Method Manual
Refrigerant HCFC & CFC Free
Exterior Powder Coated Steel
Interior Zinc Coated Galvanized Steel
Insulation Polyurethane (Ecomate) Foam
Additional Insulation Beaded Foam Sub-Lids
Lockable Lid Lockable with Padlock
Casters 6, Swivel with Locks
Storage Optional Inventory Racks
Shipping Weight 900 Lbs.

Electrical

Standard Voltage 115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug 20A | 7.3A | NEMA 5-20
(Optional Voltages) 208 Volts, 230 Volts
Power Configuration Hardwired
Certification(s) UL Rated
Certification File Number SA10711
Certification Classification Class I, Division I & II,
Groups C & D

Controller

Display Type Explosion Proof, Digital

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor