

MODEL C40-2

MINI CHEST ULTRA LOW FREEZER 0°C TO -40°C

Capacity [Cu. Ft.] 2 Cu. Ft.
Capacity [Liters] 56 Liters
Temperature Range [°C] 0°C to -40°C
Temperature Range [°F] 32°F to -40°F

Dimensions
Exterior [Inches] 25.25" x 25.75" x 40"
Interior [Inches] 17" x 14" x 14"
Exterior [Centimeters] 64 x 65 x 101
Interior [Centimeters] 43 x 35 x 35

Refrigeration System Single Stage System
Compressors 1, Hermetic Compressor
Air Circulation Gravity Flow
Defrost Method Manual
Refrigerant HCFC & CFC Free
Exterior Powder Coated Steel
Interior Zinc Coated Galvanized Steel
Insulation Polyurethane (Ecomate) Foam
Additional Insulation Beaded Foam Sub-Lids
Lockable Lid Lockable with Padlock
Porthole Optional 1/2"
Casters 4, Swivel with Locks
Storage Optional Inventory Racks
Shipping Weight 335 Lbs.

Electrical

Standard Voltage 115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug 15A | 6A | NEMA 5-15
(Optional Voltages) 208 Volts, 230 Volts
Certification(s) ETL Listed

Controller

Display Type Microprocessor, Digital
Alarms High/Low Temp, Power Failure, Low Battery
Alarm Relay Yes, Dry Contacts
Automatic Restart Yes, Automatically Restarts After Power Failure
Backup Battery Yes, Only Powers Alarm

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor