

MODEL C40-5X

EXPLOSION PROOF CHEST FREEZER 0°C TO -40°C

Capacity [Cu. Ft.] 5 Cu. Ft.
Capacity [Liters] 142 Liters
Temperature Range [°C] 0°C to -40°C
Temperature Range [°F] 32°F to -40°F

Dimensions Width x Depth x Height
Exterior [Inches] 40.5" x 35" x 43.75"
Interior [Inches] 30" x 18" x 16"
Exterior [Centimeters] 102 x 88 x 111
Interior [Centimeters] 76 x 46 x 40

Refrigeration System Single Stage System
Compressors 1, Hermetic Compressor
Compressor Container Explosion Proof
Air Circulation Gravity Flow
Defrost Method Manual
Refrigerant HCFC & CFC Free
Exterior Powder Coated Steel
Interior Zinc Coated Galvanized Steel
Insulation Polyurethane (Ecomate) Foam
Additional Insulation Beaded Foam Sub-Lids
Lockable Lid Lockable with Padlock
Casters 4, Swivel with Locks
Storage Optional Inventory Racks
Shipping Weight 525 Lbs.

Electrical

Standard Voltage 115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug 15A | 6A | NEMA 5-15
(Optional Voltages) 208 Volts, 230 Volts
Power Configuration Hardwired
Certification(s) UL Rated
Certification File Number SA10711
Certification Classification Class I, Division I & II,
Groups C & D

Controller

Display Type Explosion Proof, Digital

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor