

MODEL C80-27

CHEST ULTRA LOW FREEZER -40°C TO -80°C

Capacity [Cu. Ft.] 27 Cu. Ft.
Capacity [Liters] 766 Liters
Temperature Range [°C] -40°C to -80°C
Temperature Range [°F] -40°F to -112°F

Dimensions Width x Depth x Height
Exterior [Inches] 98" x 36" x 43.5"
Interior [Inches] 67" x 23" x 31.25"
Exterior [Centimeters] 248 x 91 x 110
Interior [Centimeters] 170 x 57 x 79

Refrigeration System Cascade-Style System
Compressors 2, Hermetic Compressors
Air Circulation Gravity Flow
Defrost Method Manual
Refrigerant HCFC & CFC Free
Exterior Powder Coated Steel
Interior Zinc Coated Galvanized Steel
Insulation Polyurethane (Ecomate) Foam
Additional Insulation Beaded Foam Sub-Lids
Lockable Lid Lockable with Padlock
Porthole Optional 1/2"
Casters 12, Swivel with Locks
Storage Optional Inventory Racks
Shipping Weight 1125 Lbs.

Electrical

Standard Voltage 115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug 20A | 15A | NEMA 5-20
(Optional Voltages) 208 Volts, 230 Volts
Certification(s) ETL Listed

Controller

Display Type Microprocessor, Digital
Alarms High/Low Temp, Power Failure, Low Battery
Alarm Relay Yes, Dry Contacts
Automatic Restart Yes, Automatically Restarts After Power Failure
Backup Battery Yes, Only Powers Alarm

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor