

MODEL C85-12X

EXPLOSION PROOF CHEST FREEZER -40°C TO -85°C

Capacity [Cu. Ft.] 12 Cu. Ft.
Capacity [Liters] 340 Liters
Temperature Range [°C] -40°C to -85°C
Temperature Range [°F] -40°F to -120°F

Dimensions
Exterior [Inches] 65.5" x 36" x 47.5"
Interior [Inches] 55" x 19" x 20"
Exterior [Centimeters] 166 x 91 x 120
Interior [Centimeters] 139 x 48 x 50

Refrigeration System Cascade-Style System
Compressors 2, Hermetic Compressors
Compressor Container Explosion Proof
Air Circulation Gravity Flow
Defrost Method Manual
Refrigerant HCFC & CFC Free
Exterior Powder Coated Steel
Interior Zinc Coated Galvanized Steel
Insulation Polyurethane (Ecomate) Foam
Additional Insulation Beaded Foam Sub-Lids
Lockable Lid Lockable with Padlock
Casters 6, Swivel with Locks
Storage Optional Inventory Racks
Shipping Weight 825 Lbs.

Electrical

Standard Voltage 115 Volts, 60 Hertz, 1 Phase
Amps / Run Amps / Plug 20A | 15A | NEMA 5-20
(Optional Voltages) 208 Volts, 230 Volts
Power Configuration Hardwired
Certification(s) UL Rated
Certification File Number SA10711
Certification Classification Class I, Division I & II,
Groups C & D

Controller

Display Type Explosion Proof, Digital

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



Warranty 1 Year Parts & Labor