BIM44GIFADARHD



32.13" x 14.63" x 22.5" (H x W x D)

ADA compliant commercially approved automatic defrost clear icemaker with internal pump and panel-ready door

Highlights:

Commercial ENERGY STAR certification

32 1/8" height for use in ADA compliant settings

Flexible design allows built-in or freestanding use in 15" wide spaces

Product Features:

15" Wide ADA Compliant Clear Icemaker	Built-in undercounter icemaker produces up to 45 lbs. of clear cubes
ENERGY STAR certified commercial performance	Efficient performance for commercial use
ADA compliant	32 1/8" height fits under lower ADA compliant counters
Commercially approved	ETL-S listed to NSF-12 standards for use in commercial environments
Built-in pump	Internal pump allows more flexibility in placing the unit
Built-in capable	Make the best use of space by installing your appliance under the counter
Panel-ready door	Stainless steel door frame accepts full overlay panels to match adjacent cabinetry (panel size: 27" H x 14 1/2" W and at least 3/4" thick; maximum weight: 10 lbs.)
Clear ice cube production	Clear cubes offer the perfect cooling of your beverages; NOTE: ice is produced in sheets and can easily be broken into cubes using the provided scoop
Automatic defrost	Reduced maintenance with auto defrost system

BIM44GIFADARHD Specifications:

Overview	
Height of Cabinet	31.88" (81 cm)
Height to Hinge Cap	32.13" (82 cm)
Width	14.63" (37 cm)
Depth	22.5" (57 cm)
Depth with Panel	23.25" (59 cm)
Depth with door at 90°	36.25" (92 cm)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	2.5
Plug Type	NEMA 5-15P
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101093192
Icemaker	
Door Swing	RHD
Drain Required	Yes
Daily Ice Production	45.0 lbs. (20 kg)
Ice Storage Capacity	25.0 lbs. (11 kg)
Ice Shape	Cube
Size of Cube	7/8" x 7/8" x 7/8"
Number of Ice Cube Sizes	1
Interior Light	Yes
Fan Type	Exterior
Refrigerant Type	R290a
Refrigerant Amount	1.87 oz.
High Side PSI	286.0
Low Side PSI	110.0
Interior Height	18.75" (48 cm)
Interior Width	11.25" (29 cm)
Interior Depth	15.5" (39 cm)
Level Legs	4



SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799 info@summitappliance.com **www.summitappliance.com**